

Excavadoras de ruedas



DX210w



20600 kg
0,51 ~ 1,28 m³
120 kW / 2000 rpm

DX190w



18840 kg
0,38 ~ 0,93 m³
116 kW / 1900 rpm

DX170w



16930 kg
0,32 ~ 0,90 m³
103 kW / 2000 rpm



DX160w



16020 kg
0,24 ~ 0,76 m³
99 kW / 2000 rpm

DX140w



14060 kg
0,24 ~ 0,76 m³
99 kW / 2000 rpm

DX55w



5550 kg
0,175 m³
40,8 kW / 2400 rpm

EXCAVADORAS DE ORUGAS		Unidad	DX55W	DX140w		DX160w		DX170w		DX190w		DX210w	
				Mono Boom	Arti Boom	Mono Boom	Arti Boom	Mono Boom	Arti Boom	Mono Boom	Arti Boom	Mono Boom	Arti Boom
Peso operativo		kg	5550	14060	14570	16020	16460	16930	17480	18840	18260	20600	20800
Capacidad del cazo (SAE)		m ³	0,175	0,24 ~ 0,76	0,24 ~ 0,76	0,24 ~ 0,76	0,24 ~ 0,76	0,32 ~ 0,90	0,32 ~ 0,90	0,38 ~ 0,93	0,38 ~ 0,93	0,51 ~ 1,28	0,51 ~ 1,28
Velocidad		km/h	10 ~ 30	10 ~ 37	10 ~ 37	10 ~ 37	10 ~ 37	10 ~ 37	10 ~ 37	10 ~ 36	10 ~ 36	9 ~ 36	9 ~ 36
Motor	Modelo	—	Yanmar, 4TNV98-E	Doosan DL06	Doosan DL06	Doosan DL06	Doosan DL06	Doosan DL06	Doosan DL06	Doosan DL06	Doosan DL06	Doosan DL06	Doosan DL06
	Potencia	CV / rpm	54,7 / 2400	132 / 2000	132 / 2000	132 / 2000	132 / 2000	138 / 2000	138 / 2000	155 / 1900	155 / 1900	162 / 2000	162 / 2000
		kW / rpm	40,8 / 2400	99 / 2000	99 / 2000	99 / 2000	99 / 2000	103 / 2000	103 / 2000	116 / 1900	116 / 1900	120 / 2000	120 / 2000
Gama de trabajo	Alcance de excavación	mm	6110	7520	8750	8250	8750	8885	9095	9200	9530	10000	9405
	Profundidad de excavación	mm	3495	4580	5530	5190	5530	5410	5755	5965	5900	6255	5625
	Altura de excavación	mm	5980	8130	9520	8850	9520	9125	10020	9340	10510	10050	10560
Dimensiones	Longitud total	mm	6120	7235	6885	7470	6885	8200	8325	8659	8610	9400	9210
	Ancho total	mm	1920	2496	2496	2496	2496	2496	2496	2496	2496	2500	2500
	Altura total	mm	2855	3351	3734	3460	3730	3190	3077	3310	3360	3490	3140